

E-19



▶ FEATURES

- Exceptionally elegant exterior
- Stylish rear side design
- Swift 3ms response time
- Crisp 1000 contrast ratio
- NeoV Optical Glass™
- Dual digital and analog inputs
- Built-in speakers with headphone jack
- Auto-adjustment for optimal setting
- Intuitive OSD with key lock function
- Kensington® security socket
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19.0" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	1000:1 (Typical)
	Surface Treatments	Hard Coating (2H), Anti-glare Treatment
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Color	16.7M
	Response Time	3ms (GTG)
	Frequency (H/V)	H: 24kHz - 80kHz V: 56Hz - 75Hz
	Max. Pixel Clock	135MHz
Input	Life Time	50,000hrs (Typical)
	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	3.5mm Audio Line-in
	Audio Out	3.5mm Headphone Jack
	Speaker	1W x 2
Connector	Power	3-Pin AC Plug
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	+5° ~ +25°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, EPA, GOST, NOM, WEEE, RoHS
	VESA	DDC 2B, DPMS
	Power AC Consumption	100 - 240V, 50 - 60Hz <55W (On) <2W (Stand-by) <1W (Off)
Dimensions	Net (W x H x D)	437 x 450 x 196mm (17.2" x 17.7" x 7.7")
	Packing (W x H x D)	555 x 580 x 171mm (21.9" x 22.8" x 6.7")
Weight	Net Weight	7.3Kg (16.1lbs)
	Gross Weight	9.5Kg (21.0lbs)
Packing	1 Pallet	30 Cartons
	20' Container	360 Sets
	40' Container	720 Sets

All specifications are subject to change without prior notice