



KEY FEATURES

- 2D Comb Filter
- Connectivity - RGB, S-VIDEO, BNC 2 In / 2 Out
- Multi Language OSD Support
- Most Advanced LCD Panel Applied
- 250 NITS, 500:1

SPECIFICATION

DRAWING

Model		PCML8
Display	Screen Size	8"
	Resolution	800 x 600@75Hz
	Pixel Pitch	0.2025 x 0.2025 mm
	Brightness	250cd/m ²
	Contrast Ratio	500:1
	Aspect Ratio	4 : 3
	Viewing Angle(H/V)	140°/120°
	Display Color	16.2 Million
	Response Time	< 25ms
	Video System	NTSC / PAL
Interface	Video In/ Out(BNC Type)	2 / 2
	S-Video In/ Out	1 / 0
	VGA In (15Pin D-Sub)	1
	Component	N/A
	DVI-D In/ HDMI In	N/A
	Audio In (RCA Type)	1
	PC Stereo In	1
Audio	Built in Speakers	Yes(2W X 2)
Transmitter	Remote Control	N/A
Special Features	Multi Display Function	N/A
	Filter Type	2D Comb filter
	Deinterlacing	N/A
	Trigger Source Switching	Yes (NO / NC)
	LCD Protection Glass	N/A
	Noise Reduction Control (NR)	N/A
	Auto Source Sequencing	N/A
Cabinet	Cabinet color / Base Stand	Black / Yes
	Cabinet Material	Electronic galvanized Iron
Regulations		CE
Power	Consumption : < On	<20W
	Electrical Ratings	AC100 ~ 240V(50/60Hz) DC 12V / 1.5A
Circumstance	Operating Temperature	0 ~ 50°C
	Storage Temperature	-30 ~ 80°C
Mounts	VESA Mounts Size	75 x 75 mm

