

X-15



▶ FEATURES

- Distinctive metal housing for added strength
- NeoV Optical Glass™
- Swift 8ms response time
- High 400 cd/m² brightness
- Crisp 3000:1 dynamic contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- Auto-adjustment for optimal settings
- Kensington® security socket
- VESA standard wall mount
- Available colours: black, white

▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	15.0" (381mm)
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297mm
	Brightness	400cd/m ² (Typical)
	Contrast Ratio	3000:1 (DCR)
	Viewing Angle (H/V)	140°/125° (Typical)
	Display Color	16.7M
	Response Time	8ms (GTG)
	Frequency (H/V)	H: 30kHz - 60kHz V: 56Hz - 75Hz
Input	Max. Pixel Clock	80MHz
	Life Time	50,000hrs (Minimum)
	Analog	15-Pin D-Sub
	Digital	24-Pin DVI-D
Connector	S-Video	4-Pin Mini Din S-Video
	CVBS	CVBS Jack
	Power	3-pin AC Plug
	NeoV Optical Glass	Thickness
Tilt	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	0° ~ +20°	
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Certifications & Compliance	FCC, UL/CUL, TUV/Baurt, CE, BSMI, CB, ISO 13406-2,GOST, EPA, NOM, TUV-S, WEEE, RoHS
	VESA	DDC-2B, DDC-CI, DPMS
	Power AC Consumption	100 - 240V, 50 - 60Hz <22W (on) <2W (Stand-by) <1W (Off)
Dimensions	Net (W x H x D)	380 x 359 x 155mm (15.0" x 14.1" x 6.1")
	Packing (W x H x D)	488 x 447 x 219mm (19.2" x 17.6" x 8.6")
Weight	Net Weight	4.8Kg (10.6lbs)
	Gross Weight	7.4Kg (16.3lbs)
Packing	1 Pallet	40 Cartons
	20' Container	480 Sets
	40' Container	1040 Sets

All specifications are subject to change without prior notice

