

## ENTRANCE PANEL

## EAN: 5060514913468 (SILVER)

BAS-IP AV-04SD — stylish vandal-proof panels with installation by the wall mount method.

This individual entrance panel is suitable for installation both in apartments and in the office, factory, gas station, etc.



SILVER

## Main features

- Panel type: Individual.
- Camera: 1/4".
- Resolution: 2 Mpx.
- Camera angle: 100° (horizontal).
- Output video: HD (1280 × 720), H.264 Main Profile.
- Night backlight: 6 LEDs.
- Light sensitivity: 0,01 LuX.
- Protection class: IP64.
- IK-Code: IK09.
- Working temperature: -40 +65 °C.
- Power consumption: 6,5 W, in standby 3,6 W.
- Power supply: PoE, +12 V DC.
- Body: Aluminum.
- Colors: Silver.
- Dimensions: 84 × 170 × 31 mm.
- Installation: Surface mount.



## Functionality

- Interface: Multi-language graphical and WEB interface.
- Lock opening:
  - By means of a monitor
  - By QR code
  - By guest link
  - The BAS-IP Intercom app
  - The BAS-IP Link app
  - From API
- Shortcut buttons: 1 mechanical call button.
- Authentication: Separate password for settings,
- WEB interface and RTSP stream.
- Talking mode: Full duplex.
- Additionally:
  - Software Link support
- SIP P2P
- Built-in relay
- Open API

